

Bullard

It's your life and you're worth it™

EDP16TE

AIR FLOW: 16 cfm at 5 psig. Supplies air to three workers wearing continuous-flow, supplied-air half or full face mask respirators, or two workers wearing a continuous-flow, supplied-air hood or helmet style respirator.

Supplied-air respirators used with this pump must be NIOSH approved to operate at 15 psig or less.

Operates with a totally enclosed fan cooled motor. For use in oily, moist or dusty conditions.

Inlet Filter: Medium efficiency, keeps particles larger than 25 microns out of the air supply. Inlet filter can be extended up to 300 feet from the pump using V50IN and V50EX remote extension hose kits.

Outlet Filter: Carbofine with activated carbon

Weight: 98 lbs.


Dimensions: 14" wide x 28" long x 16" high.

EDP16HAZ

Same features as EDP16TE plus:

Hazardous-duty motor complies with National Electric Code requirements for hazardous atmospheres.

Thermal overload and starter/contactors to be provided by the user.



EDP16TE



EDP30

EDP30

AIR FLOW: 30 cfm at 10 psig. Supplies air to six workers wearing continuous-flow, supplied-air half or full face mask respirators, or four workers wearing a continuous-flow, supplied-air hood or helmet style respirator.

Will also supply cool air to two workers using Bullard's Frigatron® 2000 air conditioner with certain NIOSH-approved Bullard hood-style respirators.

Supplied-air respirators used with this pump must be NIOSH approved to operate at 30 psig or less.

Air supply hose quick-disconnect pod can be extended 300 feet from pump using V60 extension hose kits.

Open drip-proof motor drive, for use in clean, dry areas.

Inlet Filter: Medium efficiency, keeps particles larger than 25 microns out of the air supply.

Outlet Filter: Carbofine with activated carbon

Weight: 292 lbs.

Dimensions: 26" wide x 38" long x 32" high.

EDP50

AIR FLOW: 50 cfm at 10 psig. Supplies air to ten workers wearing continuous-flow, supplied-air half or full face mask respirators, or seven workers wearing a continuous-flow, supplied-air hood or helmet style respirator.

Supplied-air respirators used with this pump must be NIOSH approved to operate at 15 psig or less.

Air supply hose quick-disconnect pod can be extended 300 feet from pump using V60 extension hose kits.

Open drip-proof motor drive, for use in clean, dry areas.

Inlet Filter: Medium efficiency, keeps particles larger than 25 microns out of the air supply.


Outlet Filter: Carbofine with activated carbon

Weight: 292 lbs.

Dimensions: 26" wide x 38" long x 32" high.



EDP50



EDP10

EDP10

AIR FLOW: 10 cfm at 5 psig. Supplies air to two workers wearing continuous-flow, supplied-air half or full face mask respirators, or one worker wearing a continuous-flow, supplied-air hood or helmet style respirator.

Supplied-air respirators used with this pump must be NIOSH approved to operate at 15 psig or less.

Open drip-proof motor drive, for use in clean, dry areas.

Inlet Filter: Medium efficiency, keeps particles larger than 25 microns out of the air supply. Inlet filter can be extended up to 300 feet from the pump using V50IN and V50EX remote extension hose kits.

Outlet Filter: Carbofine with activated carbon

Weight: 49 lbs.

Dimensions: 8" wide x 16.3" long x 13.5" high.

DISTRIBUTED BY: POLY-SOURCE INDUSTRIES INC.

#1 - 19725 Telegraph Trail

Langley, BC

Canada V1M 3E6

Tel: 604-888-3505 Fax: 604-888-3503