

LARGE ELECTRIC AIRLESS SPRAYER SPECIFICATIONS

		Ultra Max II 695		Ultra Max II 795		Ultra Max II 1095			Ultra Max II 1595		
SPECIFICATIONS	Maximum Tip Size	0.031		0.033		0.035			0.039		
	Maximum psi (bar)	3300 (227)		3300 (227)		3300 (227)			3300 (227)		
	Maximum gpm (lpm)	0.95 (3.6)		1.10 (4.1)		1.20 (4.5)			1.35 (5.1)		
	MaxPower Motor hp	2.0 Brushless DC		2.2 Brushless DC		2.4 Brushless DC			2.8 Brushless DC		
	Control	SmartControl 3.0		SmartControl 3.0		SmartControl 3.0			SmartControl 3.0		
	Weight lb (kg)	93 (42) Standard Hi-Boy		98 (44) Standard		120 (55) Standard			125 (56) Standard		
	Gun Support: 1 Gun 2 Guns 3 Guns	0.031 0.023 —		0.033 0.025 0.019		0.035 0.027 0.021			0.039 0.029 0.023		
SERIES TYPE		STANDARD	PROCONTRACTOR	STANDARD	PROCONTRACTOR	STANDARD	PROCONTRACTOR	IRONMAN	STANDARD	PROCONTRACTOR	IRONMAN
MODEL	Cart Design— Part Number	Hi-Boy—16W892 Lo-Boy—16W893	16W894	16W895	16W896	16W899	16W900	16W901	16W902 (Canada) 16W936	16W903 (Canada) 16W937	16W907 (Canada) 16W938
INCLUDES	Gun	Contractor		Contractor		Contractor		Silver Plus	Contractor		Silver Plus
	Hose	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless		1/4 in x 50 ft (6.4 mm x 15 m) AND 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless		1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless		1/4 in x 50 ft (6.4 mm x 15 m) AND 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) AND 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless		1/4 in x 50 ft (6.4 mm x 15 m) AND 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless
	Tip	RAC X 517		RAC X 517		RAC X 517		RAC X 517, RAC X Wide RAC 1231	RAC X 517		RAC X 517, RAC X Wide RAC 1231
	Filter	60 Mesh Easy Out		60 Mesh Easy Out		60 Mesh Easy Out		60 Mesh Easy Out	60 Mesh Easy Out		60 Mesh Easy Out
PUMP	Type	QuikChange System		ProConnect System		QuikChange System		ProConnect System	QuikChange System		ProConnect System
	Rod	Chromex		Chromex		Chromex		MaxLife	Chromex		MaxLife
	Sleeve	Hardened SST		Hardened SST		Hardened SST		MaxLife	Hardened SST		MaxLife
ADDITIONAL SERIES FEATURES		—		QuikReel		—		QuikReel	—		Roll Cage Frame
		—		FastFlush		—		FastFlush	—		FastFlush
		—		LED Display		—		LED Display	—		LED Display
		—		WatchDog		—		WatchDog	—		WatchDog
		—		On-Board Toolbox		—		On-Board Toolbox	—		Flat-Proof Tires
WEAR PARTS	Replacement Pump	16Y598		16X414		16Y706		16X420	16Y706		16X420
	Repair Kit	248212		248212		248213		248213/16X430*	248213		248213/16X430*
	Rod	248206		16X434		248207		16X436	248207		16X436
	Sleeve	248209		248209		248210		257031	248210		257031
	Intake Seat Kit	239922		239922		244199		244199	244199		244199
MANUAL	Operation	332916		332916		332916		332916	332916		332916
	Parts	332918		332918		332918		332918	332918		332918
	Pump	333028		332922		333028		332922	333028		332922

*Kit includes ceramic inlet and outlet check balls.

		TexSpray Mark IV
SPECIFICATIONS	Maximum Tip Size	0.033
	Maximum psi (bar)	3300 (227)
	Maximum gpm (lpm)	1.10 (4.1)
	Motor	MaxPower 2.2 hp Brushless DC
	Control	SmartControl 3.0
	Weight lb (kg)	108 (49)
	Compressor Air Output	Compressor and Air Atomizer Kit required for some texture finishes

		TexSpray Mark V
	Maximum Tip Size	0.039
	Maximum psi (bar)	3300 (227)
	Maximum gpm (lpm)	1.35 (5.1)
	Motor	MaxPower 2.8 hp Brushless DC
	Control	SmartControl 3.0
	Weight lb (kg)	135 (61)
	Compressor Air Output	Compressor and Air Atomizer Kit required for some texture finishes



		TexSpray Mark X 240 Volt
SPECIFICATIONS	Maximum Tip Size	0.045
	Maximum psi (bar)	3300 (227)
	Maximum gpm (lpm)	2.10 (7.9)
	Motor	MaxPower 4.0 hp Brushless DC
	Control	SmartControl 3.0
	Weight lb (kg)	142 (64)
	Compressor Air Output	Compressor and Air Atomizer Kit required for some texture finishes



SERIES TYPE		STANDARD	PROCONTRACTOR	STANDARD	PROCONTRACTOR	IRONMAN
MODEL	Part Number	16W897	16W898	16W905	16W906	16X947
	INCLUDES					
INCLUDES	Gun	FlexPlus	FlexPlus	Heavy-Duty Texture	Heavy-Duty Texture	Heavy-Duty Texture
	Hose	3/8 in x 50 ft (9.5 mm x 15 m)	3/8 in x 100 ft (9.5 mm x 30 m)	3/8 in x 50 ft (9.5 mm x 15 m)	3/8 in x 100 ft (9.5 mm x 30 m)	3/8 in x 100 ft (9.5 mm x 30 m)
	Tip(s)	RAC X 425	RAC X 425	RAC X 427 and 531	RAC X 427 and 531	RAC X 427 and 531
	Filter	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out
PUMP	Type	QuikChange System	ProConnect 2	QuikChange System	ProConnect 2	ProConnect 2
	Rod	Chromex	Chromex	Chromex	Chromex	Chromex
	Sleeve	Hardened SST	Hardened SST	Hardened SST	Hardened SST	MaxLife Extreme Duty
ADDITIONAL SERIES FEATURES		-	QuikReel	-	QuikReel	Roll Cage Frame
		-	FastFlush	-	FastFlush	LED Display
		-	LED Display	-	LED Display	WatchDog
		-	WatchDog	-	WatchDog	Flat-Proof Tires
		-	On-Board Toolbox	-	On-Board Toolbox	FastFlush
MANUAL	Operation	332916	332916	332916	332916	332916
	Parts	332918	332918	332918	332918	332918
TYPICAL APPLICATIONS	Materials Sprayed	Oil-based coatings, enamels, latex, block-fillers, elastomers, epoxies, drywall mud and other high-build materials	Oil-based coatings, enamels, latex, block-fillers, elastomers, epoxies, drywall mud and other high-build materials	Oil-based coatings, enamels, latex, block-fillers, elastomers, epoxies, drywall mud and other high-build materials	Oil-based coatings, enamels, latex, block-fillers, elastomers, epoxies, drywall mud and other high-build materials	Oil-based coatings, enamels, latex, block-fillers, elastomers, epoxies, drywall mud and other high-build materials
	Surfaces	Medium to large residential and commercial interiors and exteriors	Medium to large residential and commercial interiors and exteriors	Medium to large residential and commercial interiors and exteriors	Medium to large residential and commercial interiors and exteriors	Large commercial and industrial interiors and exteriors

SERIES TYPE		STANDARD	PROCONTRACTOR
MODEL	Part Number	16W908	16X099
	INCLUDES		
INCLUDES	Gun	Heavy-Duty Inline Texture	Heavy-Duty Inline Texture
	Hose	1/2 in x 50 ft (13 mm x 15 m)	1/2 in x 100 ft (13 mm x 30 m)
	Tip(s)	LTX531 and LTX541	LTX531 and LTX541
	Filter	60 Mesh Easy Out	60 Mesh Easy Out
PUMP	Type	QuikChange System	ProConnect 2
	Rod	Chromex	Chromex
	Sleeve	Hardened SST	Hardened SST
ADDITIONAL SERIES FEATURES		-	QuikReel
		-	-
		-	LED Display
		-	WatchDog
		-	On-Board Toolbox
MANUAL	Operation	332916	332916
	Parts	332918	332918
TYPICAL APPLICATIONS	Materials Sprayed	Oil-based coatings, enamels, latex, block-fillers, elastomers, epoxies, drywall mud and other high-build materials	Oil-based coatings, enamels, latex, block-fillers, elastomers, epoxies, drywall mud and other high-build materials
	Surfaces	Large residential and commercial interiors and exteriors	Large residential and commercial interiors and exteriors

