2K Aliphatic Urethane



Product Data Sheet

PRODUCT DESCRIPTION

70805/7952 is a high solids chemical resistant, twocomponent, polyester aliphatic polyurethane designed for use as a topcoat over flooring & wall coating systems and as the primary wearing surface when applied to properly primed concrete.

70805/7952 combines superior resistance to chemical attack, ultra-violet degradation and excellent impact and abrasion resistance. U.S.D.A. acceptable.

PRODUCT NUMBERS AND COLORS

Standard colors are: 70805-00 Clear

70805-01 White 70805-02 Gray 70805-03 Tan

70805-11 Light Gray

For special color consult NEOGARD®

CURED FILM PERFORMANCE

Description	Test Method	Results
Tensile Strength	ASTM D412	4,000 psi
Elongation	ASTM D412	10%
Permanent Set	ASTM D412	<10%
Water Resistance	ASTM D471	<1%
MVT @ 5 mils	ASTM E96	1.4
Taber Abrasion	ASTM D4060	40 mg/1,000 cs-17
Adhesion	ASTM D4541	300 psi
Flammability	ASTM D635	Pass

PRODUCT DATA

Description	Test Method	Results
Weight/Gal (mixed)	ASTM D1475	8.63 lbs/gal
Weight Solids (mixed)	ASTM D4209	62%
Volume Solids (mixed)	Calculated	58%
VOC (mixed)	EPA Method 24	335 g/L
Viscosity (mixed)	ASTM D2196	400 cps
Flash Point	ASTM D3278	102°F
Mix Ratio 70805:7952		2:1 by volume

APPLICATIONS

70805/7952 is used as a topcoat and corrosion resistant wearing surface on a variety of prepared substrates.

- Over epoxy primed concrete.
- Over trowelled resinous flooring.
- Over decorative floor systems.
- Over self-leveling systems.
- Can be used interior and exterior.
- Over WallGard high build wall systems.

For surface preparation and application instructions, refer to NEOGARD's Flooring Systems Manual for specific applications.

HEALTH AND SAFETY

Read the Material Safety Data Sheet (MSDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

Manufacturer warrants that the standards and qualities of the product described herein will not vary by more than 10% from the tested results set forth above. MANUFACTURER HEREBY EXPRESSLY DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY AND/OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Buyer must make its own determination of the suitability of any product for its use, whether such product is used alone or in combination with other materials. To the extent this or any of Manufacturer's products is proven to be defective, Buyer's sole remedy shall be limited to the replacement of such defective product, exclusive of any costs of labor. MANUFACTURER SHALL NOT BE LIABLE OR OBLIGATED FOR ANY LOSS OR CONSEQUENTIAL OR OTHER DAMAGE INCURRED DIRECTLY OR INDIRECTLY BY BUYER OR ANY OTHER PERSON OR ENTITY THAT ARISES IN ANY WAY IN RELATION TO THIS OR ANY OF MANUFACTURER'S OTHER PRODUCTS. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority of the owner of the patent. No Applicator is or should be viewed as an employee or agent of Manufacturer. 02142012/70805-7952PD.indd