Emergency CANUTEC 613-996-6666



Product:

ISOCYANATE ENERTHANE ECO ISOCYANATE 100

Revision date 09-01-2023

1895, de l'Industrie St-Mathieu de Beloeil (Québec) J3G 4S5 Tel: (450) 446-8554 Watt: (800) 561-8686 Fax: (450) 446-8557

01 :PRODUCT AND COMPANY IDENTIFICATION

Manufacturer ENERLAB 2000 INC.

1895, de l'Industrie

St-Mathieu-de-Beloeil, (Québec) J3G 4S5 Canada

Tél: (450) 446-8554 / 1-800-561-8686

Fax: (450) 446-8557

Product name Isocyanate 100

Chemical family Polymethylene polyphenylene isocyanate Use Component of a polyurethane system

Emergency telephone Canutec number 613-996-6666

02: HAZARDS IDENTIFICATION



ROUTES OF EXHIBITION EYE CONTACT, SKIN CONTACT, INHALATION

LIQUIDS, AEROSOLS OR PRODUCT VAPORS ARE IRRITATING. MAY CAUSE TEARS

EYE CONTACT REDNESS AND RASH. IF THE INJURY IS NOT TREATED, CORNEAL DAMAGE MAY OCCUR, AND THE HEALING OF THE INJURY

WILL BE SLOW. DAMAGE IS USUALLY REVERSIBLE

SKIN CONTACT IRRITATION. MAY CAUSE REDNESS, INJURY, ERUPTION, BLEEDING OR FORMATION OF BULBS

INHALATION (ACUTE)

ISOCYANATE VAPORS OR PARTICLES SPRAYED AT CONCENTRATIONS GREATER THAN PERMITABLE EXPOSURE THRESHOLD

(TLV) MAY CAUSE IRRITATION (BURNING FEELING) MUCOSAL IN THE RESPIRATORY TRACT CAUSING NASAL FLOW, CRASH,

COUGH OPPRESSION, BREAST LACK OF BREATH AND LOW PULMONARY FUNCTION. PEOPLE WITH ALREADY NON-SPECIFIC

COUGH OPPRESSION, BREAST LACK OF BREATH AND LOW PULMONARY FUNCTION. PEOPLE WITH ALREADY NON-SPECIFIC BRONCHIC HYPERACTIVITY MAY REACT IN LOW VOLUME CONCENTRATIONS WITH SYMPTOMS AND ASTHMA CRISIS. EXPOSURE TO MUCH HIGHER CONCENTRATIONS THAN TLV MAY CAUSE BRONCHITIS, BRONCHIC SPASMS, AND PULMONARY EDEEM. THESE EFFECTS ARE USUALLY REVERSIBLE. HYPERSENSITIVITY PNEUMONIA FROM CHEMICALS HAVE ALSO BEEN

REPORTED WITH SYMPTOMS SIMILAR TO INFLUENZA. THESE SYMPTOMS MAY OCCUR SEVERAL HOURS AFTER THE EXHIBITION MAY IRRITATE AND BURN MUCOSES IN GASTROINTESTINAL PATHWAYS. POSSIBLE SYMPTOMS: SOREBORNE, ABDOMINAL

PAIN, NAUSEA, VOMITING, DIARRHEA

EFFECT OF CHRONIC EXPOSURE PROLONGED CONTACT MAY CAUSE REDNESS, ENFLURY, RASH, DEQUAMATION, BULB FORMULATION AND IN CERTAIN CASES

SKIN SENSITIZATION, REPEATED OVEREXPOSURE OR SINGLE DOSE MAY CAUSE SENSITIVE SENSITIZED SENSITIZATION IN SOME PERSONS THAT THEY WILL RESPOND TO SUBSEQUENT EXPOSITIONS AT THE ISOCYANTE AT LEVELS WELL IN DEATH OF TWO TVL. THESE SYMPTOMS, WHICH MAY INCLUDE CHEST DISRUPTIONS, SIFFLANT BREATHING, COUGH, LOSS OF BLOW, OR ASTHMA CRISIS, MAY OCCUR IMMEDIATELY OR LATER. IT HAS BEEN REPORTED THAT AN SENSITIZED PERSON CAN PRESENT THESE SYMPTOMS WHEN EXPOSED TO DUST, COLD AIR OR OTHER IRRITANTS. THIS INCREASED LUNG SENSITIVITY MAY LAST FOR SEVERAL WEEKS AND IN SERIOUS CASES, SEVERAL YEARS. PROLONGED OR REPEATED EXPOSURE MAY CAUSE LUNG

DAMAGE AND LOWER PULMONARY FUNCTIONS

VO V COM CONTROL VI A CALMITTON CON INCOMEDIENTS			
HAZARDOUS INGREDIENTS	# CAS	<u>%</u>	<u>Toxicity</u>
Diisocyanate de diphénylméthane, isomeres et homologues	9016-87-9	60-100	DL50 (rat) > 10.000 mg/kg
4,4'-Diisocyanate de diphénylméthane (4,4'-MDI)	101-68-8	40-50	

04 : FIRST AID MEASURES

INHALATION AND INGESTION

INGESTION

EYE CONTACT RINSE IMMEDIATELY WITH LARGE AMOUNTS OF WATER ALTERNATIVELY WASHING EACH POWDER UNTIL ANY TRACE OF

PRODUCT HAS DISAPPEARED (ABOUT 15 MINUTES

SKIN CONTACT WASH WITH A LOT OF WATER AND SOAP. REMOVE CONTAMINATED CLOTHING, WASH CLOTHING SUBSTANTIALLY SOUGHT

EFORE REUSE

D INGESTION IN THE EVENT OF INHALATION BRING IN FRESH AIR. IF THERE IS BREATHING BREATHING PRACTICE ARTIFICIAL RESPIRATION.

IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION.

Breathing is difficult, give oxygen. Get medical attention.

DO NOT INDUCE VOMITING, DRINK 1 TO 2 CUPS OF MILK OR WATER. NEVER GIVE ORAL ADMINISTRATION TO A

PERSON UNCONSCIOUS, CONTACT A PHYSICIAN AS SOON AS POSSIBLE

ADDITIONAL INFORMATION NOTES TO PHYSICIAN: SYMPTOMATIC AND SUPPORTIVE AS NEEDED. FOLLOWING SEVERE EXPOSURE MEDICAL FOLLOW-UP

SHOULD BE MONITORED FOR AT LEAST 48 HOURS. THE FIRST AID PROCEDURE SHOULD BE ESTABLISHED IN CONSULTATION WITH THE DOCTOR RESPONSIBLE FOR INDUSTRIAL MEDICINE.

05: FIREFIGHTING MEASURES

FLASH POINT(DEG C) 198.8. PENKY-MARTENS CLOSE CUP

N/A

N/A

TEMPERATURE OF AUTO IGNITION(DEG

C)

SEUIL MAXIMAL D'INFLAMMABILITÉ N/A

MINIMUM FLAMMABILITY THRESHOLD

EXTINGUISHING MEDIA CARBON DIOXIDE, CHEMICAL POWDER, FOAM. IN CASE OF LARGE FIRE SPRAY WATER MUST BE USED

HAZARDOUS COMBUSTION PRODUCT PROTECT FROM FUMES THAT COULD BE TOXIC AND IRRITANT

SENSITIVITY TO SHOCKS AND STATIC

DISCHARGE

CLEANING

SPECIAL FIRE FIGHTING MEASURES

NOT APPLICABLE

FIREFIGHTERS MUST WEAR AN AUTONOMOUS RESPIRATORY APPARATUS TO PROTECT THEM FROM FUMES WHICH COULD BE

TOXIC AND IRRITATING. DURING A FIRE ISOCYATIVE VAPORS AND OTHER IRRITATING AND HIGHLY TOXIC GASES MAY BE RELEASED BY THERMAL DECOMPOSITION OR COMBUSTION. COOL THE CONTAINERS EXPOSED TO THE FIRE BY SPRAYING THEM WITH WATER. HEAT WILL CAUSE PRESSURE INCREASE IN CONTAINER AND EXPLOSIVE BREAKAGE MAY OCCUR

06: ACCIDENTAL RELEASE MESURES

LEAKAGE / SPILL EVACUATE ALL NON-INDISPENSABLE PERSONNEL. VENTILATE, ELIMINATE ALL IGNITION POINT. END THE PLACE TO CONTAIN

SPILL. WEAR FULL PROTECTIVE EQUIPMENT, INCLUDING THE RESPIRATORY, DURING CLEANING
IMPORTANT SPILL
IF SPILES OCCUR DURING TRANSPORTATION CALL CANUTEC AT (613) 996-6666. IF THE ISOCYANATI

IF SPILLS OCCUR DURING TRANSPORTATION, CALL CANUTEC AT (613) 996-6666. IF THE ISOCYANATE IS TEMPORARILY

CONTROLLED TO COVER THE PRODUCT SPILLED FROM PROTEIN FOAM COVERAGE, LARGE QUANTITIES MAY BE PUMPED IN

CONTAINERS CLOSED BUT NOT SEALED FOR DISPOSAL.

MINOR SPILL ABSORB ISOCYANATE WITH WOOD SAW OR OTHER ABS

ABSORB ISOCYANATE WITH WOOD SAW OR OTHER ABSORBENT MATERIAL. REMOVE TO THE SHOVEL AND PLACE THE PRODUCT IN APPROPRIATE CONTAINERS NOT SEALED. TRANSPORT TO A WELL VENTILATED PLACE (OUTSIDE) AND TREAT WITH NEUTRALIZING SOLUTION. 80% WATER MIXTURE AND NON IONIC SURFACTANT TERGITOL TMN-10 (20%), OR MIXTURE OF WATER 90%, AMMONIA CONCENTRATE (FROM 3 TO 8%) AND DETERGENT (2%). MIX THE NEUTRALIZING PRODUCT AND

ISOCYANATE IN A 10/1 RATIO. LEAVE REST TO DISCOVER FOR 48 HOURS, TO ALLOW THE CARBON DIOXIDE TO DISENGAGE.

DECONTAMINATE FLOOR FOR AT LEAST 15 MINUTES WITH DECONTAMINATION SOLUTION

07: HANDLING AND STORAGE

PROCÉDURE ET MANUTENTION AVOID CONTACT WITH SKIN AND EYES. AVOID BREATHING THE VAPORS. PRECURSOR SYMPTOMS (IRRITATION OF YEVETING

SKIN AND EYE CONTACT, AVOID BREATHING VAPORS, PRECURSOR SYMPTOMS (EYE, NOSE, THROAT AND ODOR IRRITATION) AND ODOR) ARE NOT SUFFICIENT TO AVOID OVEREXPOSURE INHALATION: EMPLOYEE INFORMATION AND STAFF TRAINING, NOSE AND THROAT, AND ODOR) ARE NOT SUFFICIENT TO AVOID OVEREXPOSURE BY INHALATION. EMPLOYEE INFORMATION

AND STAFF TRAINING MATTER

CONDITION D'ENTREPOSAGE

STORE IN A CLOSED LOCATION TO AVOID CONTAMINATION BY MOISTURE. STORE AWAY FROM ANY SOURCE OF HEAT AND

IGNITION POINT (MIN / MAX: 18/30 ° C). Do not close Hermetically if it is likely that the product is

CONTAMINATED. HEATED ISOCYANATE VAPORS CAN BE VERY DANGEROUS

08: EXPOSURE CONTROL / PERSONAL PROTECTION

EYES SAFETY GLASSES OR 8 INCH VISOR. DO NOT WEAR CONTACT LENSES

RESPIRATORY IN SUCH CASES, OR WHEN THE ISOCYANATE CONCENTRATIONS EXCEED THE EXPOSURE LIMITS, RESPIRATORY PROTECTION

SHOULD BE USED. A POSITIVE PRESSURE RESPIRATOR WITH FREE AIR OR AN INDEPENDENT RESPIRATORY APPARATUS IS RECOMMENDED. AN AIR PURIFYING RESPIRATOR IS NOT RECOMMENDED DUE TO LOW WARNING PROPERTIES, INCLUDING

SMELL OR IRRITATION OF THE PRODUCT

GLOVES GLOVES RESISTANT TO CHEMICAL PRODUCTS IN BUTYL OR NITRILE RUBBER. PRODUCE GOOD HYGIENE, WASH WELL BEFORE

HANDLING FOOD

CLOTHES AND SHOES WEAR APPROPRIATE CLOTHING AND PROTECTORS

OTHER EYE SHOWER. EMERGENCY SHOWER SHOULD BE NEARBY

VENTILATION REQUIRED WHEN ISOCYANATES ARE PROCESSED, HEATED OR SPRAYED, LOCAL VENTILATION SHOULD BE USED TO MAINTAIN

CONCENTRATIONS IN THE AIR UNDER THE TLV. WEAR AN APPROPRIATE RESPIRATORY MASK. WELL ADJUST WHEN THE LEVEL OF CONTAMINATION EXCEEDS THE PERMITABLE THRESHOLD OF EXPOSURE. AVOID BREATHING DUST. IF GENERAL OR LOCAL VENTILATIONS ARE INADEQUATE, PERSONS EXPOSED TO DRIZZLES SHOULD WEAR AN APPROPRIATE RESPIRATORY

MASK

MONITORING THE EXHIBITION VALUES SHOULD BE MONITORED BY MONITORING TECHNIQUES TO ENSURE THAT THE EXPOSURE LIMIT

VALUE (YVL) IS NOT EXCEEDED

MEDICAL SUPERVISION MEDICAL SURVEILLANCE OF ALL EMPLOYEES WHO HANDLE OR COME INTO CONTACT WITH ISOCYANATES IS RECOMMENDED.

THIS SURVEILLANCE SHOULD INCLUDE MEDICAL EXAMINATIONS AT THE TIME OF COMMITMENT AND PERIODIC

EXAMINATIONS, INCLUDING EXAMINATIONS OF RESPIRATORY FUNCTION (FEV, FVC MINIMUM). PERSONS WITH CONDITIONS OF THE ASTHMATIC GENUS, CHRONIC BRONCHITIS, OTHER CHRONIC RESPIRATORY DISEASES, ECZEMA OR SKIN

SENSITIZATION SHOULD NOT WORK WITH ISOCYANATES. ONCE A PERSON HAS ESTABLISHED ISOCYANATE SENSITIZATION, IT

SHOULD NOT BE EXPOSED TO THIS PRODUCT

09 :PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE LIQUID

ODOUR MUSTY

DENSITY 1.24@20°C

ODOUR TRESHOLD N/A

Vapour pressure < 0.00001 mmHg. @ 25 °C (DIM)

Vapour Density (AIR = 1) 8.5 (DIM) Evaporation rate N/A

BOILING POINT (760 MMHG) DECOMPOSE BEFORE BOILING

FLASH POINT >204°C

PH N/A

WATER SOLUBILITY INSOLUBLE, REACTS, CO2 FORMATION

PARTITION COEFFICIENT: N-OCTANOL/WATER REACTS WITH WATER

Freezing point (DEG. C) CRYSTALLISE BELOW 10 °C

DECOMPOSITION TEMPERATURE >230°C

VISCOSITY, DYNAMIC 150-220 CPS @ 25°C

10: STABILITY AND REACTIVITY

HAZARDOUS REACTIONS CONTACT WITH MOISTURE, ALKALI, TERTIARY AMINES, METAL COMPOUNDS OR OTHER PRODUCTS THAT

CAN REACT WITH ISOCYANATES, OR AT HIGH TEMPERATURES. MAY CAUSE POLYMERIZATION.

STABILITY STABLE UNDER RECOMMENDED STORAGE CONDITIONS

CHEMICAL INCOMPATIBILITY

WATER, AMINES, STRONG BASES, ALCOHOLS, CAUSE CORROSION TO COPPER AND ALUMINUM ALLOYS

HAZARDOUS DECOMPOSITION

PRODUCTS

WATER, AMINES, STRONG BASES, ALCOHOLS, CAUSE CORROSION TO COPPER AND ALUMINUM ALLOYS

BY FIRE AND HEAT: CARBON MONOXIDE, NITROGEN OXIDE, HYDROGEN CYANIDE, CARBON DIXIDE

11: TOXICOLOGICAL INFORMATION

ACUTE ORAL TOXICITY (DL50) > 10.000 MG/KG (RAT)DERMAL TOXICITY (DL50) > 9.400 Mg/KG (LAPIN)

INHALATION (CL50) POLYMER: 490 Mg/m³ (RAT). MONOMERIC: 2240 Mg/m³ (RAT).

IRRITATION BY PRODUCT
MAY CAUSE MODERATE EYE IRRITATION AND LIGHT AND TEMPORARY CORNEAL INJURIES

SENSITIZATION SKIN CONTACT MAY CAUSE SKIN ALLERGIC REACTION. STUDIES ON ANIMALS HAVE REVEALED THAT SKIN CONTACT

WITH ISOCYANATES CAN PLAY A ROLE IN RESPIRATORY SENSITIZATION

CARCINOGENICITY PULMONARY TUMORS HAVE BEEN RECORDED IN LABORATORY ANIMALS EXPOSED TO DROPS FROM MDI AEROSOLS AND

POLYMERIC MDI (6 MG / M3) DURING ALL THEIR LIVES. CURRENT EXPOSURE LIMITS SHOULD PROTECT AGAINST THESE

EFFECTS

MUTAGENICITY MDI WAS LOWLY POSITIVE IN SOME IN VITRO STUDIES. OTHER IN VITRO STUDIES HAVE BEEN NEGATIVE. MUTAGENICITY

STUDIES ON ANIMALS HAVE BEEN MAINLY NEGATIVE

REPRODUCTIVE TOXICITY NO DATA FOUND

12: ECOLOGICAL INFORMATION

TOXICITY TO FISH CL50 > 1000 mg/L

TIME 24 H

SPECIES DANIO RERIO

13: DISPOSAL CONSIDERATION

DISPOSAL SPILLED AND RINSING WATER IS CLASSIFIED CHEMICAL WASTE AND MUST BE DISPOSED OF ACCORDING

TO MUNICIPAL, PROVINCIAL AND FEDERAL REGULATIONS. INCINERATION IS THE PREFERRED METHOD. EMPTY CONTAINERS MUST BE HANDLING CAREFULLY WITH RESIDUES. DECONTAMINATE CONTAINERS BEFORE DISPOSING. DECONTAMINATED EMPTY CONTAINERS SHOULD BE CRUSHED TO AVOID THEIR REUSE. DO NOT HEAT OR CUT EMPTY CONTAINERS WITH AN ELECTRICAL OR GAS TORCH. VAPORS AND

GASES MAY BE TOXIC

14: TRANSPORT INFORMATION

TDG NOT DANGEROUS GOODS

15: REGULATORY INFORMATION

WHMIS CLASSIFICATION

CONTROL D2A. D2B. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA UNDER THE CONTROLLED PRODUCTS REGULATIONS AND MATERIAL SAFETY DATA SHEET CONTAINS THE INFORMATION REQUIRED BY THE CONTROLLED PRODUCTS REGULATIONS

16: OTHER INFORMATION

NOTE

THIS INFORMATION, WHICH IS GIVEN WITH NO WARRANTY, EXPRESS OR IMPLIED, IS BASED ON KNOWLEDGE AND APPLIES ONLY TO THE PRODUCT LISTED. ENERLAB 2000 INC. DISCLAIMS ANY LEGAL RESPONSIBILITY FOR THE USE AND RELIABILITY OF THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET

PREPARATION DATE: FEB. 2018